International Journal of Engineering, Management and Humanities (IJEMH)
Volume 7, Issue 1, Jan.-Feb., 2026 pp: 64-73 ISSN: 2584-2145 www.ijemh.com

Harnessing Biogas from Soak-Away Pits: A Pathway to Clean Energy and Improved Sanitation

Chinaza Esther Mbaeke[1]*, S. I. Oluka[2]
[1] *Department of Biomedical Engineering, Enugu State University of Science and Technology*
[2] *Department of Agricultural and Bio-Resources Engineering, Enugu State University of Science and Technology.*

Date of Submission: 05-01-2026 Date of Acceptance: 16-01-2026

Abstract
Soak-away pits, common in rural and peri-urban sanitation systems, produce methane-rich biogas through anaerobic digestion of human waste and organic residues. Traditionally viewed only as effluent disposal structures, these pits represent untapped energy resources. Capturing and utilizing their gas can simultaneously reduce greenhouse gas emissions, enhance household energy security, and improve sanitation outcomes. A typical 5-person household, for instance, could displace up to 38 kg of LPG annually while avoiding 1.57 tCO_2e methane emissions, whereas a 150-student hostel could prevent 15–47 tCO_2e/year and meet a significant share of cooking energy demand. This article synthesizes evidence from scientific literature, field case studies, and international guidelines, and proposes a practical framework for harnessing soak-away pit gas. It explores microbial processes, retrofit and design options, safety management—including hydrogen sulfide (H_2S) removal—socio-cultural acceptance, and policy frameworks. Practical implementation checklists and case insights from Africa and Asia are included. The paper concludes with recommendations for scaling this technology in low- and middle-income countries, particularly Nigeria.

Keywords: soak-away pits, biogas, anaerobic digestion, sanitation safety planning, methane recovery, Nigeria

I. Introduction

Access to affordable, reliable, and clean household energy remains a pressing challenge across low- and middle-income countries, especially in Sub-Saharan Africa and South Asia. At the same time, the improper management of wastewater and fecal sludge from households and institutions poses major environmental and health risks. Soak-away pits—also called leach pits or soak pits—are widely used onsite sanitation solutions, often in combination with septic tanks. Under anaerobic conditions, microbial digestion of human waste in these pits produces methane (CH_4), carbon dioxide (CO_2), and trace gases, collectively known as biogas.

Globally, methane emissions from sanitation and wastewater contribute an estimated 2–3% of total anthropogenic CH_4, a share projected to rise as urban populations grow and waste infrastructure lags. This makes sanitation-linked methane both a challenge and an opportunity: capturing it can directly mitigate climate change while delivering energy co-benefits.

Methane is a potent greenhouse gas but also a valuable clean-burning fuel. Harnessing it from soak-away pits creates a dual benefit: mitigating climate emissions while substituting expensive or polluting fuels such as wood, charcoal, and kerosene. Properly engineered systems reduce odors, minimize uncontrolled emissions, and generate a renewable cooking gas for households and institutions. However, unmanaged soak-away gas poses hazards, notably explosion risk, asphyxiation, and H_2S toxicity.

For Nigeria, the relevance is immediate. Over 70% of households rely on solid biomass for cooking, driving deforestation, household air pollution, and energy poverty. Meanwhile, more than 46 million Nigerians lack access to safely managed sanitation. Converting soak-away pits into safe, productive biogas systems directly advances SDG 7 (Affordable and Clean Energy) and SDG 6 (Clean Water and Sanitation), offering an integrated solution to two of the country's most persistent development gaps.

This article explores the feasibility of such conversion, integrating microbial fundamentals, design principles, safety protocols, policy contexts, and case studies to outline a pathway for cleaner energy and better sanitation.

II. Scientific Basis of Gas Formation

2.1 Anaerobic Digestion Stages

Biogas production in soak-away pits results from anaerobic digestion, a microbial process

International Journal of Engineering, Management and Humanities (IJEMH)
Volume 7, Issue 1, Jan.-Feb., 2026 pp: 64-73 ISSN: 2584-2145 www.ijemh.com

where organic matter decomposes in an oxygen-free environment. This digestion occurs through four sequential stages: hydrolysis, acidogenesis, acetogenesis, and methanogenesis. In the hydrolysis phase, complex organic polymers such as carbohydrates, proteins, and lipids are enzymatically broken down into simpler molecules like sugars, amino acids, and fatty acids. During acidogenesis, acidogenic bacteria ferment these simpler compounds to produce volatile fatty acids (VFAs), hydrogen (H_2), and carbon dioxide (CO_2). The acetogenesis stage involves the conversion of VFAs into acetate, hydrogen, and CO_2 by acetogenic bacteria, which are critical substrates for methane production. Finally, methanogenesis is performed by methanogenic archaea, which convert acetate and hydrogen into methane (CH_4) and CO_2. This multistage process stabilizes organic matter and generates a combustible gas mixture that can be harnessed for energy recovery (Khanal et al., 2017; Angelidaki et al., 2018).

The biogas produced typically contains 50–70% methane, 30–50% CO_2, and trace amounts of hydrogen sulfide (H_2S) and ammonia (NH_3), making it a valuable renewable energy source when effectively captured and utilized. The efficiency of biogas production depends on factors such as temperature, pH, organic loading rates, and the composition of the microbial communities involved. Table 1 presents the typical biogas composition in soak-away pit systems. A clear understanding of these digestion stages and controlling environmental conditions can enhance gas yields and reduce the environmental risks associated with untreated organic waste (Sun et al., 2019; Li et al., 2021).

Table 1: Typical Composition of Biogas from Anaerobic Digestion

Gas Component	Percentage (%)
Methane (CH_4)	50–70
Carbon Dioxide (CO_2)	30–50
Hydrogen Sulfide (H_2S)	0–3
Ammonia (NH_3)	Trace (<1)

2.2 Conditions in Soak-Away Pits

Anaerobic digestion operates most efficiently under controlled mesophilic conditions, typically within a temperature range of 30 °C to 38 °C, a neutral pH (6.8–7.4), and a hydraulic retention time (HRT) of 20–40 days**.** These parameters foster the metabolic activities of hydrolytic, acidogenic, acetogenic, and methanogenic microbes responsible for breaking down organic waste and producing methane. Deviations from these optimal conditions can significantly reduce microbial activity, particularly among methanogens, thereby lowering gas yields and compromising process stability (Wikipedia, 2025; Kothari et al., 2014). A recent study emphasized that maintaining temperature between 33–36 °C and pH between 6.5–7.2 led to improved and consistent methane production in mesophilic digesters (Tandfonline, 2024).

In contrast, soak-away pits, which are primarily designed for the passive disposal of fecal sludge and wastewater, lack such environmental control. Nevertheless, their moist and oxygen-deprived environment inadvertently supports partial anaerobic digestion. While this can lead to some biogas generation, the absence of containment and gas collection infrastructure results in methane (CH_4) and hydrogen sulfide (H_2S) emissions directly into the environment. This uncontrolled release not only contributes to greenhouse gas emissions but also causes odour nuisances and public health concerns**.** Retrofitting soak-away pits with impermeable linings**,** low-cost gas capture systems, or transitioning to biodigester-based sanitation technologies can mitigate these environmental impacts and enhance energy recovery (Tandfonline, 2024).

International Journal of Engineering, Management and Humanities (IJEMH)
Volume 7, Issue 1, Jan.-Feb., 2026 pp: 64-73 ISSN: 2584-2145 www.ijemh.com

III. Design and Engineering Options

3.1 Retrofit Options





a. Schematic of biogas capture and treatment systems
b. A schematic diagram of a soak-away retrofit with gas capture

Sealing with airtight domes incorporating gas ports and pressure relief valves

To efficiently capture biogas from soak-away pits, retrofits often begin by sealing the pit with a durable cover, such as a reinforced concrete slab or prefabricated dome. These structures create an anaerobic "chamber," preventing gas loss and creating a controlled environment for gas collection. Built-in gas ports allow for safe extraction, while relief valves mitigate overpressure—reducing the risk of structural failure or hazardous leaks (BioCycle, 2016).

Installing with condensate traps

Transporting biogas safely requires corrosion-resistant pipelines made from HDPE or uPVC. These lines must include condensate traps at low points to capture moisture as biogas cools, preventing blockages and preserving system safety. Biocycle (2016) recommends maintaining a slope of at least 2% and installing automatic drip traps every 200–250 feet to avoid flow obstructions and protect downstream equipment.

Adding H_2S scrubbers and moisture removal units

Raw biogas often contains harmful hydrogen sulfide (H_2S) and moisture, both of which can damage appliances. To address this, systems may incorporate biological H_2S scrubbers or iron sponge media**,** achieving removal efficiencies up to 98%, while requiring minimal maintenance (CRA, n.d.; Biogas Products Ltd., n.d.). Such units ensure safer and cleaner gas for household or small-scale use.

Ensuring safe effluent discharge via soak trenches or constructed wetlands

Post-digestion effluent needs proper handling to avoid environmental contamination. Routing effluent into constructed wetlands offers an effective, eco-friendly treatment: vegetation and microbial action reduce pathogenic load and nutrient concentrations, making the effluent suitable for reuse—especially valuable in water-scarce areas (IWA Publishing, 2024).

3.2 New Hybrid Designs



Biodigester-septic hybrid system

International Journal of Engineering, Management and Humanities (IJEMH)
Volume 7, Issue 1, Jan.-Feb., 2026 pp: 64-73 ISSN: 2584-2145 www.ijemh.com

For new on-site sanitation systems, biodigester–septic hybrid designs offer a sustainable approach by combining anaerobic digestion with biogas recovery in a single integrated structure. These systems usually consist of dual chambers—one designated for primary digestion and separation of solids, and the other for further treatment of effluent. A gas dome, fixed or floating, is installed over the digestion chamber and fitted with pressure relief valves to safely capture and regulate biogas emissions. The inclusion of internal baffles helps increase the retention time of waste, thereby enhancing the efficiency of digestion and maximizing methane production. These hybrid systems not only improve the breakdown of organic waste but also reduce odor and environmental contamination, while offering the added benefit of on-site renewable energy generation, especially in off-grid or low-income areas. As highlighted by Tilley et al. (2014), such integrated designs are well-suited for peri-urban communities seeking sustainable sanitation solutions that also support energy self-sufficiency.

3.3 Gas Cleaning and Upgrading

Biogas produced from soak-away pits or hybrid biodigesters typically contains impurities such as hydrogen sulfide (H_2S), carbon dioxide (CO_2), moisture, and siloxanes, which must be removed before the gas can be used effectively. For household cooking applications, basic cleaning is generally sufficient. This includes moisture removal, achieved using condensate traps or passive drying systems, and H_2S scrubbing, often using iron oxide, activated carbon**,** or ferrous filters, to prevent corrosion and foul odors. These low-cost solutions significantly improve the safety and efficiency of biogas for domestic use, especially in rural or peri-urban settings where advanced equipment may not be accessible.

However, in cases where higher purity biomethane is required—for example, for bottling, vehicle fuel, or injection into natural gas grids—more advanced upgrading techniques are necessary. These include water scrubbing, which uses water under pressure to absorb CO_2 and H_2S; membrane separation, which selectively filters out CO_2 molecules; and pressure swing adsorption (PSA), a method that separates gases under varying pressures using adsorbent materials (Angelidaki et al., 2018). These methods can raise methane purity levels to over 95%, making the gas suitable for a wider range of commercial and industrial applications (Sun et al., 2015). While costlier and more complex, these technologies are increasingly being integrated into centralized biogas facilities in developing regions as the demand for clean energy grows.

IV. Safety and Risk Management

The use of biogas in domestic and small-scale applications demands adherence to strict safety protocols due to the flammable and toxic nature of its components. Methane (CH_4), which constitutes the bulk of biogas, becomes explosive when mixed with air at concentrations between 5% and 15%, while hydrogen sulfide (H_2S) is acutely toxic, with exposure levels above 100 ppm posing severe health risks, including respiratory paralysis and death (Ajayi & Balusu, 2017; OSHA, 2020).

Installing flame arrestors and non-return valves at the inlets of biogas appliances is essential to prevent flame flashback and gas backflow, both of which can lead to explosions or fires. Flame arrestors work by dissipating heat from a flame front, preventing it from traveling back into the biogas line, while non-return valves ensure unidirectional gas flow, especially critical in low-pressure systems. These devices are standard in international safety codes for domestic gas installations.

Leak testing is another critical safety practice. Users and technicians should routinely check for leaks using soap solution, which forms visible bubbles at leak points, or with portable gas detectors that can sense methane or H_2S even at low concentrations. Regular testing helps prevent accidental ignition and toxic exposure, especially in enclosed or poorly ventilated space.

Confined-space entry protocols must be strictly followed before entering biodigesters, sealed pits, or gas chambers. These spaces can contain lethal concentrations of H_2S**,** CO_2**,** or methane, which displace oxygen and cause asphyxiation. International standards recommend the use of gas monitors, personal protective equipment (PPE), and the presence of a standby observer trained in confined-space rescue procedures (WHO, 2015).

User education is equally important. Operators and household members should be trained to recognize the characteristic "rotten-egg" smell of H_2S and understand immediate actions in case of suspected gas leaks, such as ventilating the area, turning off gas valves, and avoiding open flames. Such awareness significantly reduces the risk of accidents in biogas-using households (Tilley et al., 2014).

The **World Health Organization's Sanitation Safety Planning (SSP) framework** provides a systematic approach to identifying and managing health risks throughout the sanitation service chain—including biogas systems. It emphasizes

International Journal of Engineering, Management and Humanities (IJEMH)
Volume 7, Issue 1, Jan.-Feb., 2026 pp: 64-73 ISSN: 2584-2145 www.ijemh.com

hazard identification, exposure assessment, risk mitigation, and monitoring, making it a valuable tool for institutions and communities adopting biogas technologies (WHO, 2015).

V. Applications and Energy Potential

This section gives illustrative, evidence-based projections of biogas volumes, energy yield, and avoided emissions for typical households, institutional hostels, and small communities. All projections use conservative ranges and explicit assumptions so readers can adapt them to local conditions.

Key assumptions

- Faeces-based biogas yield per adult: 0.03–0.06 m^3 CH_4-rich biogas per day.
- Household size (example): 5 persons.
- Energy equivalence: 1 m^3 biogas ≈ 6 kWh (useful thermal energy) and ≈ 0.43 kg LPG equivalent.
- Capture (collection + system) efficiency: 50–80% (range to account for leakage, incomplete capture, system downtime).
- Methane mass density: ≈ 0.716 kg CH_4 per m^3 (at near-STP).
- Global Warming Potential (GWP100) used: 25

All arithmetic below is shown so readers can follow or re-run with alternate assumptions.

5.1 Household-scale (example household = 5 people)

1. Daily raw biogas production
   - Lower: 0.03 m^3/adult/day × 5 adults = 0.03 × 5 = 0.15 m^3/day.
   - Upper: 0.06 m^3/adult/day × 5 adults = 0.06 × 5 = 0.30 m^3/day.
2. Annual raw biogas production
   - Lower: 0.15 m^3/day × 365 = 54.75 m^3/year.
   - Upper: 0.30 m^3/day × 365 = 109.50 m^3/year.
3. Captured (usable) biogas at 50–80% capture efficiency
   - Lower captured: 54.75 × 0.50 = 27.375 m^3/year.
   - Upper captured: 109.50 × 0.80 = 87.60 m^3/year.
4. Useful energy (kWh) from captured gas
   - Lower: 27.375 m^3 × 6 kWh/m^3 = 164.25 kWh/year.
   - Upper: 87.60 m^3 × 6 kWh/m^3 = 525.60 kWh/year.
5. LPG equivalent displaced
   - Lower: 27.375 m^3 × 0.43 kg LPG/m^3 = 11.77 kg LPG/year.
   - Upper: 87.60 m^3 × 0.43 kg LPG/m^3 = 37.67 kg LPG/year.
6. Avoided methane emissions (CO_2e) if captured instead of released
   - Methane mass captured (kg) = captured m^3 × 0.716 kg CH_4/m^3.
     - Lower mass: 27.375 × 0.716 = 19.6005 kg CH_4/year.
     - Upper mass: 87.60 × 0.716 = 62.716 kg CH_4/year.
   - CO_2e avoided = CH_4 mass × GWP100 (25):
     - Lower CO_2e: 19.6005 × 25 = 490.01 kg CO_2e/year.
     - Upper CO_2e: 62.716 × 25 = 1,568.04 kg CO_2e/year.

Interpretation (household): A 5-person household with an effectively captured soak-away system could realistically obtain ~160–526 kWh/year of useful thermal energy — equivalent to ~12–38 kg LPG/year — while preventing ~0.49–1.57 tonnes CO_2e/year of methane emissions. In many Nigerian contexts this can meaningfully displace a portion of household cooking fuel (particularly when combined with improved stove efficiency), and contributes a measurable climate mitigation benefit.

5.2 Institutional example — hostel with 150 students

Using the same per-person yield and capture assumptions:

1. Annual raw biogas
   - Lower raw: 0.03 × 150 × 365 = 1,642.5 m^3/year.
   - Upper raw: 0.06 × 150 × 365 = 3,285.0 m^3/year.
2. Captured biogas (50–80%)
   - Lower captured: 1,642.5 × 0.50 = 821.25 m^3/year.
   - Upper captured: 3,285.0 × 0.80 = 2,628.0 m^3/year.
3. Useful energy (kWh)
   - Lower: 821.25 × 6 = 4,927.5 kWh/year.
   - Upper: 2,628.0 × 6 = 15,768.0 kWh/year.
4. CO_2e avoided
   - Lower: 821.25 × 0.716 × 25 = 14,700.38 kg CO_2e/year (≈14.7 tCO_2e/year).
   - Upper: 2,628.0 × 0.716 × 25 = 47,041.20 kg CO_2e/year (≈47.0 tCO_2e/year).

Interpretation (hostel): A 150-student facility could realistically capture ~0.82–2.63×10^3 m^3/year of biogas — enough for ~5–16 MWh/year of thermal energy, often sufficient to meet a substantial share of

International Journal of Engineering, Management and Humanities (IJEMH)
Volume 7, Issue 1, Jan.-Feb., 2026 pp: 64-73 ISSN: 2584-2145 www.ijemh.com

institutional cooking energy needs (shared kitchens) and yielding ~15–47 tCO_2e/year of avoided methane emissions.

5.3 Community example — 100 households

Scaling the household example to a small community (100 households of 5 people):

1. Captured biogas
   - Lower: 27.375 m^3/household × 100 = 2,737.5 m^3/year.
   - Upper: 87.60 m^3/household × 100 = 8,760.0 m^3/year.
2. Useful energy (kWh)
   - Lower: 2,737.5 × 6 = 16,425 kWh/year (≈16.4 MWh/year).
   - Upper: 8,760.0 × 6 = 52,560 kWh/year (≈52.6 MWh/year).
3. CO_2e avoided
   - Lower: 2,737.5 × 0.716 × 25 = 49,001.25 kg CO_2e/year (≈49.0 tCO_2e/year).
   - Upper: 8,760.0 × 0.716 × 25 = 156,804.00 kg CO_2e/year (≈156.8 tCO_2e/year).

Interpretation (small community): A 100-household community that successfully captures soak-away biogas can produce tens of MWh/year of thermal energy and avoid ~50–157 tCO_2e/year, making community-scale capture attractive both for energy access and for aggregated climate benefits.

Table 2. Estimated Biogas Yields, Energy Potential, and Emissions Avoided from Soak-Away Gas Capture

Scale (example)	Captured Biogas (m^3/year)	Useful Energy (kWh/year)	LPG Equivalent (kg/year)	Methane Avoided (kg CH_4/year)	Emissions Avoided (tCO_2e/year)
Household (5 persons)	27 – 88	164 – 526	12 – 38	20 – 63	0.49 – 1.57
Hostel (150 students)	821 – 2,628	4,928 – 15,768	353 – 1,131	588 – 1,881	14.7 – 47.0
Community (100 households, ~500 persons)	2,738 – 8,760	16,425 – 52,560	1,177 – 3,767	1,960 – 6,271	49.0 – 156.8



Bar charts showing biogas potential, energy potential, and emissions avoided across household, hostel, and community scales.

5.4 Notes, uncertainties and practical caveats

1. These projections are illustrative and should be adapted to local data (faeces production, co-digestion with kitchen/organic waste, temperatures, pH, desludging frequency, and actual capture efficiency).
2. Capture efficiency (50–80%) is a key lever: improving seals, reducing leaks, and ensuring continuous piping and valves can move projects toward the upper end of the range.
3. Real systems often benefit from co-digestion (food/kitchen waste, agricultural residues) which can raise per-person yields beyond the faeces-only values used here. Conversely, heavy dilution (large greywater flows) or frequent desludging can lower yields.
4. Energy use must be matched to demand patterns; biogas is best used close to generation (cooking,

International Journal of Engineering, Management and Humanities (IJEMH)
Volume 7, Issue 1, Jan.-Feb., 2026 pp: 64-73 ISSN: 2584-2145 www.ijemh.com

institutional kitchens). For storage or higher-value uses (bottling, vehicle fuel), upgrading and compression add cost and losses.
5. Emission avoidance calculations assume methane would otherwise be released to atmosphere. If methane is flared instead of used, climate benefits are reduced but still present ($CH_4 \rightarrow CO_2$ conversion).

5.5 Short checklist for applying these projections in the field

1. Measure or estimate: users per pit, daily waste input, and presence of co-substrates.
2. Run the above arithmetic with local numbers (replace 0.03–0.06 m^3/adult/day if you have site measurements).
3. Estimate capture efficiency from site survey (seal quality, piping, emissions).
4. Translate captured m^3 to energy (×6 kWh/m^3) and LPG equivalent (×0.43 kg/m^3).
5. Assess safety upgrades and gas cleaning needs before linking to stoves.

VI. Socio-Economic and Environmental Benefits

6.1 Environmental Gains:

Capturing methane through biodigester or soak-away retrofits significantly reduces greenhouse gas emissions, particularly methane (CH_4), which is over 25 times more potent than CO_2 in trapping heat over a 100-year period. In addition to climate benefits, improved containment of human waste also prevents groundwater contamination and supports better sanitation outcomes in densely populated or flood-prone areas. Furthermore, reducing open defecation and leaching from latrines minimizes pathogen spread in the environment (UNEP, 2019).

6.2 Economic Savings:

Households using biogas for cooking can realize substantial fuel cost savings, depending on previous expenditures on firewood, charcoal, or liquefied petroleum gas (LPG). Additionally, the digestate by-product of anaerobic digestion serves as a potent organic fertilizer, helping to reduce costs for smallholder farmers.

Table 3: Energy Equivalence of 1 m^3 of Biogas Compared with Common Household Fuels

Fuel Type	Average Energy Content	Equivalent to 1 m^3 Biogas (~6 kWh)	Typical Household Use Case
Firewood	4.0 kWh/kg (air-dried)	≈ 1.5 kg firewood	Boiling ~10–12 liters of water
Charcoal	7.0 kWh/kg	≈ 0.9 kg charcoal	Cooking a family meal for 4–5 persons
LPG (butane/propane mix)	12.5 kWh/kg (~26 MJ/kg)	≈ 0.48 kg LPG (≈0.9 liters)	One full day of cooking for a 5-person household
Kerosene	11.8 kWh/kg (~43 MJ/liter, density 0.8 kg/l)	≈ 0.51 kg kerosene (≈0.64 liters)	Preparing 2–3 hot meals on a wick stove
Electricity	1 kWh/unit	≈ 6 kWh electricity	Running a 1 kW hotplate for 6 hours

6.3 Health Improvements:

Switching from traditional biomass fuels to biogas significantly reduces indoor air pollution, one of the leading causes of respiratory diseases in low-income households. Clean combustion eliminates smoke, carbon monoxide, and particulate matter, thereby decreasing the incidence of asthma, chronic bronchitis, and other respiratory illnesses—especially among women and children who spend the most time near cooking areas (WHO, 2016).

6.4 Gender and Social Impact:

Biogas adoption improves gender equity by easing the domestic burden on women, who are often responsible for gathering fuel and cooking. The use of biogas reduces time and physical effort spent collecting firewood, which can be redirected toward income-generating activities or education. Health improvements due to cleaner indoor environments also enhance women's well-being and reduce caregiving demands (ENERGIA, 2019).

6.5 Local Economy:

Biogas system deployment stimulates local job creation in construction, maintenance, and user training. From masons and plumbers to biogas technicians and agricultural extension workers, the entire value chain supports small enterprises and rural livelihoods. This economic stimulation fosters community ownership, builds local capacity, and

International Journal of Engineering, Management and Humanities (IJEMH)
Volume 7, Issue 1, Jan.-Feb., 2026 pp: 64-73 ISSN: 2584-2145 www.ijemh.com

promotes long-term sustainability of the systems (IRENA, 2018).

VII. Challenges and Limitations

Despite the appeal of biogas systems in decentralized sanitation and energy models, several technical and operational challenges persist. For instance, blockages in inlets and outlets are common due to the accumulation of non-biodegradable materials and poor waste segregation, which can reduce gas production or cause full system failure. Additionally, gas leakage due to substandard sealing or inferior construction materials can compromise both safety and efficiency. A major technical concern also lies in seasonal temperature variations—as anaerobic digestion performs optimally between 30–38°C. In colder months, microbial activity slows, leading to reduced biogas yield. A study in Bangladesh found that methane content dropped from 61% in autumn to 56% in winter, while hydrogen sulfide (H_2S) levels increased, due to microbial imbalance at lower temperatures (Zaman et al., 2021). Effective insulation, passive solar heating, or heat-exchange systems have been proposed as solutions to stabilize internal temperatures (Garkoti et al., 2024).

Beyond technical limitations**,** socio-cultural and financial barriers also inhibit large-scale adoption. Safety risks**,** including the potential for gas explosions or exposure to H_2S, remain high when biogas is not adequately scrubbed or safely stored. Moreover, many communities are still reluctant to adopt systems linked to human excreta due to strong cultural taboos. However, research conducted in India revealed that this resistance is nuanced and often tied to a lack of exposure or misunderstanding of the technology; targeted community engagement and demonstration projects were found to increase acceptance significantly (Williams et al., 2022). On the economic front, the initial retrofitting cost may be prohibitive for low-income households, particularly in the absence of microfinance, government subsidies, or cooperative investment models. These financial hurdles underscore the need for integrated policy, education, and financing mechanisms to support sustainable uptake.

VIII. Case Study – Institutional Biogas in Nigerian and Indian Conditions

In Nigeria, institutional biogas implementation has proven feasible and impactful, particularly within educational and correctional facilities. At the Federal University of Technology, Akure (FUTA), a 150 kW biogas plant was commissioned in 2017, using agricultural residues and kitchen waste to supply clean energy, manage organic waste, and reduce dependence on fossil fuels. The project stands out for its success in co-digestion and structured operations, setting a model for academic institutions across the country. Similarly, since 2018, the United Nations Industrial Development Organization (UNIDO) has supported biogas systems in Nigerian correctional facilities, where human and organic waste are digested to provide gas for cooking and improve sanitation conditions.

South Asia has been a global pioneer in linking on-site sanitation to biogas recovery. In **India**, more than 4.5 million family-sized biogas plants have been installed under the National Biogas and Manure Management Programme (NBMMP), with many linked directly to pour-flush toilets. These systems divert human waste into small digesters, producing cooking gas for daily household use while simultaneously addressing sanitation challenges.

These projects underscore key success factors including co-digestion of multiple waste streams, community involvement, and ongoing maintenance support (My Engineers, 2024).

IX. Policy and Future Directions

Government policies play a critical role in scaling up biogas adoption by creating enabling environments that address financial, technical, and regulatory barriers. Incorporating biogas-ready septic and soak-away standards into national building codes ensures that new sanitation infrastructure can be easily retrofitted or built with gas capture capabilities, reducing methane emissions and enhancing energy recovery (IEA, 2021). Furthermore, offering subsidies, rebates, and incentives for retrofitting existing pits and installing biodigesters can lower upfront costs and encourage household and institutional adoption (IRENA, 2022). Financial innovations such as results-based financing and micro-credit schemes tailored to low-income communities are essential to overcome economic barriers and improve access to clean cooking fuels (WHO, 2021). Integrating biogas into broader clean-cooking initiatives and national climate action plans also leverages synergies between health, energy, and environmental goals, enabling multi-sectoral collaboration and funding (UNEP, 2023).

Emerging opportunities in technology and integration promise to further enhance the value proposition of biogas systems. For example,

coupling biogas production with solar micro-grids can stabilize energy supply in off-grid areas by providing complementary renewable energy sources and increasing system resilience (IRENA, 2022). The development of modular, scalable gas upgrading kits enables households and institutions to purify biogas to biomethane quality suitable for broader energy applications, including vehicle fuel and grid injection (IEA Bioenergy, 2023). Additionally, advances in digital monitoring and IoT sensors facilitate real-time tracking of methane and hydrogen sulfide levels, improving safety, optimizing digester performance, and enabling predictive maintenance (World Bank, 2022). These innovations, coupled with supportive policies, can accelerate the transition towards sustainable and decentralized energy solutions that mitigate climate change while improving sanitation and livelihoods.

X. Conclusion

Harnessing gas from soak-away pits is technically feasible, socially beneficial, and environmentally urgent. With modest investment and community engagement, households and institutions can convert sanitation liabilities into valuable energy resources. Adoption requires careful engineering, strong safety management, and supportive policy frameworks. When combined with awareness campaigns and financial mechanisms, soak-away biogas can play a transformative role in sustainable development across Nigeria and beyond.

References

[1]. Ajayi, T., & Balusu, R. (2017). Biogas safety and regulation. *International Journal of Environmental Science and Development, 8*(5), 356–360.

[2]. Angelidaki, I., Treu, L., Tsapekos, P., Luo, G., Campanaro, S., Wenzel, H., & Kougias, P. G. (2018). Biogas upgrading and utilization: Current status and perspectives. *Biotechnology Advances, 36*(2), 452–466. https://doi.org/10.1016/j.biotechadv.2018.01.011

[3]. BioCycle. (2016, June 15). Biogas piping design and safety fundamentals. *BioCycle*. https://www.biocycle.net/2016/06/15/biogas-piping-design-safety/

[4]. Biogas Products Ltd. (n.d.). *H_2S scrubber – Biological*. https://www.biogasproducts.co.uk/project/biogas-biological-scrubber/

[5]. Combustion Research Associates (CRA). (n.d.). *Biological H_2S scrubber—SulphPur®*. https://www.cra.energy/biological-scrubber-biogas

[6]. Garkoti, P., Ni, J. Q., & Thengane, S. K. (2024). Energy management for maintaining anaerobic digestion temperature in biogas plants. *Renewable and Sustainable Energy Reviews*. https://doi.org/10.1016/j.rser.2024.113251

[7]. IEA. (2020). *An introduction to biogas and biomethane*. Paris: International Energy Agency.

[8]. IEA Bioenergy. (2022). *Task 37 end-of-triennium report 2019–2021*.

[9]. IEA Bioenergy. (2023). *Gas Upgrading Technologies for Biomethane Production*. https://www.ieabioenergy.com/publications

[10]. IEA Bioenergy. (2025). *Technologies for flexible bioenergy*. Task 44 Report (with Task 37 data).

[11]. International Energy Agency (IEA). (2021). *Biogas for a sustainable future*. Paris: IEA.

[12]. International Renewable Energy Agency (IRENA). (2022). *Renewable energy and jobs – Annual review 2022*. Abu Dhabi: IRENA.

[13]. Khanal, S. K., Surendra, K. C., & Lee, M. (2017). Anaerobic digestion of organic solid waste. *Progress in Energy and Combustion Science, 61*, 172–193. https://doi.org/10.1016/j.pecs.2017.06.002

[14]. Kothari, R., Tyagi, V. V., Pathak, A., & Pandey, A. (2014). Important operating parameters in anaerobic digestion process. *1Library*. https://1library.net/document/yj5dld2q-important-operating-parameters-in-the-ad-process.html

[15]. Li, Y., Zhang, R., & Ma, H. (2021). Microbial community and methane production in anaerobic digestion: A review. *Environmental Science and Pollution Research, 28*, 46944–46958. https://doi.org/10.1007/s11356-021-16113-7

[16]. LPELC. (2019). *Anaerobic digesters and biogas safety*. Livestock and Poultry Environmental Learning Community.

[17]. My Engineers. (2024). *Report of biogas projects in Nigeria as at 2024, including FUTA and UNIDO prison biogas initiatives*. https://www.myengineers.com.ng/2024/07/31/report-of-biogas-projects-in-nigeria-as-at-2024

[18]. Occupational Safety and Health Administration (OSHA). (2020). *Hydrogen sulfide: Health effects*. https://www.osha.gov

[19]. Occupational Safety and Health Administration (OSHA). (2024). *Hydrogen sulfide – Hazards/Overview*. https://www.osha.gov

[20]. Sun, L., Yu, Z., Wang, Y., & Yu, L. (2019). Effect of pH and temperature on anaerobic digestion performance and microbial community structure. *Applied Energy, 239*, 143–150. https://doi.org/10.1016/j.apenergy.2019.01.061

[21]. Sun, Q., Li, H., Yan, J., Liu, L., Yu, Z., & Yu, X. (2015). Selection of appropriate biogas upgrading technology—A review of biogas cleaning, upgrading and utilization. *Renewable and Sustainable Energy Reviews, 51*, 521–532.

[22]. SuSanA/WHO. (2022). *Sanitation safety planning – Manual for safe use and disposal of excreta and wastewater* (2nd ed.). World Health Organization.

[23]. Tandfonline. (2024). Temperature and pH optimization in mesophilic anaerobic digestion for enhanced biogas production. *Biofuels*. https://www.tandfonline.com/doi/full/10.1080/17597269.2024.2447159

[24]. United Nations Environment Programme (UNEP). (2023). *Climate Action and Sustainable Energy Solutions*. Nairobi: UNEP.

[25]. Williams, B. N., Quilliam, R. S., Campbell, B., Raha, D., et al. (2022). Challenging perceptions of socio-cultural rejection of a taboo technology: Narratives of imagined transitions to domestic toilet linked biogas in India. *Energy Research & Social Science, 92*, 102802. https://doi.org/10.1016/j.erss.2022.102802

[26]. World Bank. (2022). *Digital Solutions for Sustainable Energy*. Washington, DC: World Bank.

[27]. World Health Organization (WHO). (2021). *Clean cooking and health: A global priority*. Geneva: WHO.

[28]. World Health Organization (WHO). (2022). *Sanitation safety planning – Manual for safe use and disposal of excreta and wastewater* (2nd ed.).

[29]. Zaman, M. F. U., Alam, M. M., & Sarker, S. (2021). Effects of seasonal temperature variation on slurry temperature and biogas composition of a commercial fixed dome anaerobic digester used in Bangladesh. *Sustainability, 13*(19), 11096. https://doi.org/10.3390/su131911096